

Datasheet for: AL0052

Product Type: 3P+N Isolating Delta Star

15kVA 3P+N 440V to 440/254v Wired in Delta Star configuration
60Hz



| | |
|--------------------|---|
| VA | 15000 |
| Input Voltage | 440 |
| Input Termination | Terminals M6 Studs |
| Input Current | 20.94 |
| amps | 20.94 |
| Output Voltage | 440 |
| Output Notes | 440V/254V |
| Output Termination | terminals M6 Studs |
| Product Case | T4 Industrial floor mounting case IP44 |
| Dimension | Ht:450 W:450 L:600 |
| Weight | 120kg |
| Surge Protection | SL35 30A Surge Limitor |
| Product Type | Transformer Conforms to EN61558-2-6 CE & RoHS |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product AL0052 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
15/04/2026



