

Datasheet for: 3PHD10627

**Product Type: 3P Isolating Delta Delta** 

10kva 3P Delta Delta 400v to 200v Hardwired



VA 10000 Input Voltage 400

Input Termination M5 Brass studs

Input Current 14.45 amps 28.9 Output Voltage 200

Output Termination M5 Brass studs

Product Case P6 Industrial floor/wall mounting case IP23

Dimension Ht:454 L: 384 W:305 (mm)

Weight 65kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation .04

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PHD10627 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

05/05/2025

