

Datasheet for: 3PHD15720

Product Type: 3P Isolating Delta Delta

15kva 3P Delta Delta 400v to 480v Hardwired



VA	15000
Input Voltage	400
Input Termination	M6 Brass studs
Input Current	21.7
amps	18
Output Voltage	480
Output Termination	M6 Brass studs
Product Case	T3 Industrial floor/wall mounting case IP23
Dimension	Ht:500 L: 525 W:450 (mm)
Weight	95kg
Product Type	Isolating transformer
Standard	Conforms to EN61558-2-6 CE & RoHS
Regulation	4%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product 3PHD15720 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
24/02/2026


