

Datasheet for: 3PHD30944

**Product Type: 3P Isolating Delta Delta** 

30kva 3P Delta Delta 230v to 220v Hardwired



VA 30000

Input Voltage 230

Input Termination M12 Brass studs

Input Current 75.40 amps 78.82 Output Voltage 220

Output Termination M12 Brass studs

Product Case T4 Industrial floor/wall mounting case IP23

Dimension Ht:600 L: 625 W:500 (mm)

Weight 160kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation .04

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PHD30944 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025

