

## Datasheet for: 3PTS05472

## Product Type: 3P+N Isolating Delta Star

5kva 3P Delta Star 380v to 400v Hardwired



| VA                 | 5000  |
|--------------------|---|
| Input Voltage      | 380   |
| Input Termination  | 3 way screw terminals                                   |
| Input Current      | 7.61  |
| amps               | 7.23  |
| Output Voltage     | 400   |
| Output Notes       | Line to Line 400v Line to neutral 230vac                |
| Output Termination | 3 way screw terminals                                   |
| Product Case       | P6 Industrial floor/wall mounting case IP23             |
| Dimension          | Ht:454 L: 384 W:305 (mm)                                |
| Weight             | 42kg  |
| Product Type       | Isolating transformer Conforms to EN61558-2-6 CE & RoHS |
| Regulation         | 5.5%  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product 3PTS05472 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 05/05/2025

www.airlinktransformers.com - VAT No. 573 1888 10 Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478 14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS 01279 431865 | sales@airlinktransformers.com