

Datasheet for: 3PTSD20847

Product Type: 3P+N Isolating Delta Star

20kva 3P Delta Star 415v to 220v Hardwired

VA 20000 Input Voltage 415

Input Termination M8 Brass studs

Input Current 27.86 amps 52.55 Output Voltage 220

Output Notes Line to Line 220v Line to Neutral 127v

Output Termination M8 Brass studs

Product Case T3 Industrial floor/wall mounting case IP23

Dimension Ht:500 L: 525 W:450 (mm)

Weight 135kg

Product Type Isolating transformer Conforms to EN61558-2-6 CE & RoHS

Regulation 4.0%

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product 3PTSD20847 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105deaC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025



01279 431865 | sales@airlinktransformers.com