

## Datasheet for: 3PAD0225

### Product Type: 3P+PE Auto Delta Delta

20kVA 3P 400-200v Hardwired



VA	20000
Input Voltage	400
Input Termination	Screw terminals
Input Current	28.88
amps	57.72
Output Voltage	200
Output Termination	Screw terminals
Product Case	P7 Industrial floor/wall mounting case IP23
Dimension	Ht:480 W:334 L:438
Weight	82kg
Surge Protection	SL35 Surge Limitor
Product Type	Autowound transformer Conforms to EN61558-2-13 CE & RoHS

**Commodity code:** 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



**Declaration of Conformity:** Airlink Transformers declare that the product 3PAD0225 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
05/05/2025

A handwritten signature in black ink, likely of the exporter or a representative of Airlink Transformers.

[www.airlinktransformers.com](http://www.airlinktransformers.com) - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478  
14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS  
01279 431865 | [sales@airlinktransformers.com](mailto:sales@airlinktransformers.com)