

Datasheet for: CM0120240

**Product Type: Standard Range Toroidal** 

**Transformers** 

120VA 230v to 2x40v

VA 120 Input Voltage 230

Input Termination 200mm Flexible leads 24/.2

Input Current 0.52 amps 1.5 Output Voltage 40+40

Output Termination 200mm Flexible leads 32/.2

Dimension OD: 88 Ht: 46mm

Weight 1.2kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.11

Fixing Hardware 2x 70mm Neoprene pads + steel dish washer with bolt

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM0120240 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025



www.airlinktransformers.com - VAT No. 573 1888 10

Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478

14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS

01279 431865 | sales@airlinktransformers.com