

## Datasheet for: CM0750175

### Product Type: Standard Range Toroidal Transformers

750VA 230v to 2X115v



VA	750
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	3.2
amps	3.4
Output Voltage	115+115
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 140 Ht: 75mm
Weight	5.5kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.05
Fixing	Hardware 2x110mm Neoprene pads + steel dish washer with bolt M8 75mm

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

**Declaration of Conformity:** Airlink Transformers declare that the product CM0750175 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.  
15/04/2026



