



Datasheet for: CM2000433

Product Type: Standard Range Toroidal Transformers

2000VA 230v to 4x33v

VA	2000
Input Voltage	230
Input Termination	200mm Flexible leads 16awg
Input Current	8.699999999999999
amps	15.2
Output Voltage	33+33+33+33
Output Termination	200mm Flexible leads 16awg
Dimension	OD: 195 Ht: 85mm
Weight	12kg
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Regulation	0.03
Fixing	Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM2000433 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 15/04/2026



[Handwritten signature]

