

Datasheet for: CM5000210

**Product Type: Standard Range Toroidal** 

**Transformers** 

5000VA 230v to 2x100v

VA 5000 Input Voltage 230

Input Termination 200mm Flexible leads 14awg

Input Current 21.7 amps 25 Output Voltage 100+100

Output voltage 100+100

Output Termination 200mm Flexible leads 14awg

Dimension OD: 240 Ht: 110mm

Weight 22kg

Product Type Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS

Regulation 0.03

Fixing Potted centre Drilled 10mm

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM5000210 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025



