

Datasheet for: WM7529

**Product Type: Enclosed isolating** 

transformers

7500VA 230v to 120v Hardwired



VA 7500 Input Voltage 230

Input Termination 3 x M6 Studs

Input Current 33 amps 62.5 Output Voltage 120

Output Termination Terminal Posts

Product Case P6 Industrial floor/wall mounting case IP23

Dimension Ht:454 L: 384 W:305 (mm)

Weight 45kg

Primary Protection MCB 2P 40amp type C Surge Protection MS35 50A Surge Limiter

Product Type Safety Isolating transformer Conforms to EN61558-2-06 CE & RoHS

Regulation 0.02

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product WM7529 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin.

