

Datasheet for: ST6000

Product Type: Heavy Duty 110v Portable transformers

6000 VA 230v to 2x16A & 1x32A 110V SKT 5000VA Continuous Auto transformer

VA 6000 Input Voltage 230

Input Termination 2 meter mains lead (without plug)

Input Current 26 amps 32 Output Voltage 110

Output Notes 5000va continuous rating

Output Termination 2 x 16A & 1 x 32amp Yellow sockets

Product Case 801 Tough GRP case with carrying handle IP44

Dimension Ht:280 W:340 D:260

Weight 26kg

Primary Protection Push to reset circuit breaker SP30

Surge Protection SL35 Surge Limiter
Product Type Autowound transformer

Notes This is an Autowound transformer 110v (No CTE Ground Centre Tap)

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product ST6000 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.

