



Datasheet for: WP0254

Product Type: Outdoor Waterproof Transformers

250VA 230v to Single 24v Waterproof transformer

VA	250
Input Voltage	230
Input Termination	TB04 2way screw terminal Large 76A
Input Current	1.08695652173913
amps	10.4166666666667
Output Voltage	24
Output Termination	TB03 2way screw terminal Medium 24A
Product Case	601 Black Durable reinforced waterproof case IP67
Dimension	Ht:185 W:160 L:160
Weight	4kg
Primary Protection	MO3 Self resetting Thermal-current cutout
Surge Protection	SL15 Surge Limitor
Product Type	Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS
Notes	Two waterproof glands supplied loose

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product WP0254 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
13/04/2026



