

## Datasheet for: CM0120124

## Product Type: Standard Range Toroidal Transformers

120VA 230V to 24V



| VA                 | 120  |
|--------------------|--|
| Input Voltage      | 230  |
| Input Termination  | 200mm Flexible leads 18awg UL1015                            |
| Input Current      | 0.52   |
| amps               | 5  |
| Output Voltage     | 24   |
| Output Termination | 200mm Flexible leads 16awg UL1015                            |
| Dimension          | OD: 88 Ht: 46mm  |
| Weight             | 1.2kg  |
| Product Type       | Safety Isolating transformer                                 |
| Standard           | Conforms to EN61558-2-06 CE & RoHS                           |
| Regulation         | 0.11   |
| Fixing             | Hardware 2x 70mm Neoprene pads + steel dish washer with bolt |
|                    |  |

Commodity code: 851539130

**RoHS Certificate:** Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM0120124 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025

www.airlinktransformers.com - VAT No. 573 1888 10 Airlink Transformers is a trading name of Albury Services Ltd company reg No 2666478 14 Capital Place, Lovet Road, The Pinnacles, Harlow, Essex, UK, CM19 5AS 01279 431865 | sales@airlinktransformers.com