

Datasheet for: CM6000290

**Product Type: Standard Range Toroidal** 

**Transformers** 

6000VA 230V to 2 x 90V

VA 6000 Input Voltage 230

Input Termination 200mm Flexible leads 12awg

Input Current 26 amps 66 Output Voltage 90 + 90Output Notes

2 x 90V @ 33A

Output Termination 200mm Flexible leads 12awg

Dimension OD: 240 Ht: 120mm

Weight 31kg

Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS Product Type

Regulation 0.03

Potted & Centre Drilled 12mm Fixing

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ethere Difenil Polybromurate (PEDE)







Declaration of Conformity: Airlink Transformers declare that the product CM6000290 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A

**Declaration by the Exporter:** The exporter of the product covered by this document declares that these products are of EU preferential origin. 21/06/2025

