



Datasheet for: CM6000370

Product Type: Standard Range Toroidal Transformers

6000VA 230V to 2x70V + 12V

| | |
|--------------------|-----------------------------------------------------------------|
| VA | 6000 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 12awg |
| Input Current | 26 |
| amps | 42 |
| Output Voltage | 70+70 +12 |
| Output Notes | 2 x 70 @42amp 0-12v @1amp |
| Output Termination | 200mm Flexible leads 12awg |
| Dimension | OD: 240 Ht: 120mm |
| Weight | 25kg |
| Product Type | Safety Isolating transformer Conforms to EN61558-2-23 CE & RoHS |
| Regulation | 0.03 |
| Fixing | Fixing Potted centre Drilled 12mm |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Etere Difenil Polybromurate (PEDE)

Declaration of Conformity: Airlink Transformers declare that the product CM6000370 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin.
15/04/2026

