

Datasheet for: CM75001230

Product Type: Standard Range Toroidal Transformers

7500VA 230V to 230V



| | |
|--------------------|--|
| VA | 7500 |
| Input Voltage | 230 |
| Input Termination | 200mm Flexible leads 12awg |
| Input Current | 32 |
| amps | 32 |
| Output Voltage | 230 |
| Output Termination | 200mm Flexible leads 12awg |
| Dimension | OD: 270 Ht: 135mm |
| Weight | 34kg |
| Standard | Safety Isolating transformer Conforms to EN61558-2 |
| Regulation | 0.03 |
| Fixing | Potted & Centre Drilled 12mm |

Commodity code: 851539130

RoHS Certificate: Airlink Transformers certifies and testifies that all the products and goods delivered and invoiced, do not contain any of the hazardous substances as mentioned in the 2011/65/EU European directives (RoHS). Particularly these products do not contain: Heavy metals such as Pb, Cd, Cr6+ Bifenil Polybromurate (PBB) Ether Difenil Polybromurate (PEDE)



Declaration of Conformity: Airlink Transformers declare that the product CM75001230 conforms to current European safety and EMC regulation EN61558-2-6 (Safety Isolating transformer) CE & RoHS compliant. Manufactured to Class A 105degC.

Declaration by the Exporter: The exporter of the product covered by this document declares that these products are of EU preferential origin. 15/04/2026

